



February 2015

# EXPAND YOUR DECKING POSSIBILITIES

# BISON JOIST TOP FOR USE WITH JOIST & PLANK SYSTEMS

All the benefits of Bison Pedestals...

• Protect & prolong the life span of roofing and waterproofing membranes

• Replace sleeper systems that are detrimental to waterproofing membranes

• Allow air to circulate and water to flow easily to drains

• Pedestals are impervious to water

• Lower installation costs, reduced callbacks from damaged roofing

An endless choice of decking materials...

• Composite, PVC, and natural wood decking

Create the ultimate rooftop environment with Bison Innovative Products.



# Specifications

- Works with Bison Versadjust and Level.it Series Pedestals
- Attach Model JT on top of pedestal
- Fold flaps to fit 2"x or 4"x lumber
- Install decking materials
- Impervious to water, mold and freeze/thaw
- Usually ships in 1 2 business days
- Made in the U.S.A.













### 12" O.C. JOIST SPACING (DECKING SPAN)

JOIST SIZE	JOIST SPAN	BEAM SIZE	PEDESTAL SPACING
2 x 6	10′ - 0″	4 x 6 or (2) 2 x 6	24" O.C.
2 x 8	13′ - 2″	4 x 8 or (2) 2 x 8	24" O.C.
2 x 10	16′ - 10″	4 x 10 or (2) 2 x 10	24" O.C.

#### 16" O.C. JOIST SPACING (DECKING SPAN)

JOIST SIZE	JOIST SPAN	BEAM SIZE	PEDESTAL SPACING
2 x 6	9' - 1"	4 x 6 or (2) 2 x 6	24" O.C.
2 x 8	12′ - 0″	4 x 8 or (2) 2 x 8	24" O.C.
2 x 10	15' - 2"	4 x 10 or (2) 2 x 10	24" O.C.

### 24" O.C. JOIST SPACING (DECKING SPAN)

JOIST SIZE	JOIST SPAN	BEAM SIZE	PEDESTAL SPACING
2 x 6	7′ - 11″	4 x 6 or (2) 2 x 6	24" O.C.
2 x 8	10′ - 2″	4 x 8 or (2) 2 x 8	24" O.C.
2 x 10	12' - 5"	4 x 10 or (2) 2 x 10	24" O.C.

<sup>\*\*\*</sup>CHARTS ARE SHOWN USING HEM-FIR #2 LUMBER OR BETTER

Note: Decking and joist spanning capabilities vary depending on the type of wood or composite materials being used. Code requirements also vary by location. For these reasons, this chart is for convenience only and it is the installers responsibility to ensure that the deck meets code requirements.

